



APT IP Codec

Geared Up For Next-Gen Broadcasting

The APT IP Codec is a cutting-edge, professional IP stereo codec geared up with unique, market-leading technology to provide next generation broadcast performance. Innovative and feature-packed, the APT IP Codec elevates the quality of reliable, cost-effective, and accurate temporal IP audio and MPX transmission to a level never before achieved.

The proven SureStream redundancy and distributed intelligence of ScriptEasy is extended by the best compression format APT-mpX for MPX signals and the highly precise synchronization of IP streams with APT SynchroStream.

The APT IP CODEC is perfectly equipped for individual FM feed as well as multi- and single-frequency broadcasting. It is suitable for mission critical applications and provides extensive control and monitoring functions to manage your audio, data and network conditions, as well as other equipment located at the transmitter site.

With the APT IP Codec, you know you will enjoy the rock-solid performance upon which APT has earned the trust of countless broadcasters worldwide.



Benefits



IP Transport Optimization

APT IP CODECS migrate the advantages of a synchronous connection to the IP world. With SureStream, packet losses are compensated, and latency fluctuations are eliminated by SynchroStream or the NTP-based Time Alignment. The enhanced NAT traversal mode overcomes barriers and IP packets reliably reach their specified destinations.



Pristine Audio Quality & Performance

Highest signal fidelity and lowest coding delay, which we established from the beginning with Enhanced aptX, are transferred to composite/MPX transmissions with the new APtmpX algorithm.



Maximize your Cost Savings

APT products save you money. SureStream, Enhanced aptX, and APtmpX for low bitrate composite/MPX transmissions constitute an ecosystem that provides highly available and high-quality audio distribution outside of expensive transmission paths.




SURESTREAM

+10 Years Experience: Our team of engineers has extensive experience optimizing our algorithm for redundant streaming, making SureStream synonymous with reliable transmission in lossy IP networks.

Low Latency - Low Costs: SureStream enables the broadcaster to turn imperfect, but much cheaper services, into true broadcast-grade, low-latency IP connections.

Scalability and Flexibility: SureStream is the most flexible and scalable solution for content transmission protection, able to combine multiple paths from any combination of MPLS, Satellite, Microwave, xDSL and/or Cellular (4G/5G), creating a unified super robust connection to get your audio from point A to B.




SYNCHROSTREAM

Stable Latency: The GPS-based SynchroStream eliminates variable latencies of an IP network within unprecedented narrow limits. For program transmissions, a temporal synchronized connection appears like a synchronous link.

Complete Control Over Target Latency: SynchroStream requires a single setting on the IP Encoder to define the target latency to each Decoder at a transmitter site. Only one setting is required, and all Decoders are synchronized; accurate and stable to the millisecond. Fine-tuning is done at the decoder (s) in the array.

Synchronized FM Modulation: Temporal fine-tuning is the key to optimal geographic positioning of overlapping modulations of FM carriers. SynchroStream enables modulation control with the uniquely fine granularity of <50 meters in terrain.




APTmpX

Compressed Composite/MPX: APTmpX is the industry's best MPX/composite compression algorithm, that delivers the highest sound transparency over low-bitrate IP transmissions.

Lowest Bitrate, Lowest Delay: With the lowest bandwidth requirements at 300, 400 and 600 kbps, broadcasters no longer need to compromise between low bit rate and high audio quality.

APTmpX thus eliminates the two barriers that usually discourage migration to FM MPX transmission.



SCRIPT EASY

Advanced Telemetry & Facility Management

ScriptEasy is a revolutionary facility control software for connected devices, enabling the automatic correction of any critical errors that may occur. Across its intuitive web interface, ScriptEasy includes management of the GPIO, serial communications, SNMP, logic operators, live user inputs, timers, and more. This enables the "scripting" of site operations for evaluating multiple parameters and automatically engaging back up systems, while simultaneously alerting relevant technical personnel. **Integrated in the APT IP CODEC, ScriptEasy is the core technology that provides the device with its inherent "intelligence".**



Remote Production - Broadcast from everywhere


SureStream Audio Connection



SFN Application with SynchroStream using composite/MPX over AES

with Eceso FM transmitters of WorldCast Systems illustrating the synchronized digital broadcast chain:

- Target latency, STLs exactly time-aligned
- STL delay-variability compensated
- Fine-trim in nanosecond time domain
- Accurate temporal carrier modulation
- Overlap zones precisely sited in terrain



Support Level Agreement

To make sure you reap all the benefits of your broadcast investment, you can rely on the WorldCast Systems' Support Agreement program. The range of services available and with the support of our team of experts, you will benefit from maximum uptime, better performance, and overall improve your Total Cost of Ownership!

Contact your Sales Manager for more information.



APT IP CODEC rear panel with precision clock module option

Composite/MPX & AUDIO	
Asymmetric Encoding/Decoding	Independent encoding and decoding modes for send and receive for analog and digital composite/MPX or digital audio
Analog MPX I/O	Unbalanced, capacitive isolated BNC connectors for composite/MPX, level adjustment in 0.01 dBu steps
Digital Audio I/O	AES3, AES192, 24 Bit, transformer balanced, Imp. 110 Ω, XLR-Connectors
FORMATS	
Multi Algorithm Suite for Digital audio	Eapt-X 16/24bit, lin. PCM 16/20/24bit and OPUS
MPX Formats	Analog and digital lin. MPX 16/24bit, APTmpX @300/400/600 & 900 kbps
STREAMING MODES	
Stream Types	Multiple MPX or Audio Tx-Streams, UDP and RTP forwarding, Reply-to-Sender, NAT traversal mode
Unit Clock Modes	Asymmetric, master, slave, NTP-based & high precision GPS clocking (optional)
Jitter Buffer	2-5000 ms with packet re-sequencer
QoS	DiffServ (RFC2474) per stream
Redundant Streaming	SureStream Option, multi-stream packet-by-packet redundancy
Backup Feature	SD Card for file storage
MANAGEMENT	
Front Panel Display with Key navigation	
Web Browser GUI	
APT NMS	
WCS Kybio (SNMP-based Manager)	
SNMPv2c/v3	
API	
ScriptEasy	
MONITORING & ALARMS	
Adjustable Silence Detectors (Inputs & Outputs)	
Event Logs	
Alarm Relays	
SNMP Traps/Notifications	
PHYSICAL INTERFACES	
Analog MPX	Input BNC connectors (Input loop-thru), dual outputs, impedance matched
Digital I/Os on XLR	In/Outputs digital (AES3, AES192) In/Output, ext. reference Input (AES11)
Headphone	1/4" (6.3mm) Jack Socket (front) - audio monitoring
AUX Data	D9-way connector
GPIO	D15-way connectors
Network	2x RJ45
GPSDO Input (optional)	2x BNC (10MHz & 1 PPS)
AC Power	1 + 1 (optional) IEC type
DC Power	1 + 1 (optional) Power D3-way connector

NETWORK	
Dual IP Interfaces	Dual Gigabit Ethernet IEEE 802.3x, Auto MDI-X
Port Configuration	Flexible WAN and/or LAN (Management) configuration
Port Speed Setting	Full auto, restricted auto or manual
VLAN Tagging (IEEE 802.1q)	
Virtual IP Interfaces (IP Aliasing)	
Dynamic DNS	multiple clients supported
Standard Protocols	RTP/UDP, IPv4, DHCP, FTP, HTTPS, ICMP, IGMPv2/v3, SMTP, SNMPv2c/v3, NTP
Security	TLS 1.1 and higher, Service Filter and Firewall
DATA	
Serial Data	RS232 embedded up to 9,600 Baud, via UDP stream up to 115,200 Baud
GPIO	4 switch Inputs and 4 relays embedded (Eapt-X) and via UDP stream
SYNCHROSTREAM OPTION	
GPS-based precision timing function for perfect IP stream-synchronization in FM-SFN networks.	
Time Base	ext. GPSDO, 10MHz & 1 PPS
Target Latency	Encoder setting up to 1 sec.
Extended Target Latency	GPS+NTP up to 5sec.
Timing Stability	< 0.25µs
Delay Line Adjustment	Increments corresponding to < 50m field distance
MAIN CHARACTERISTICS	
Dimensions (l x h x d)	483cm x 42mm x 160mm
19", 1u rack mount	19" x 1.75" x 6.3"
Weight	1.5kg / 3.35lbs
Mains Power Supply	100-240 VAC / 50-60Hz
Power Consumption	<20VA
Env. Temperatures	0°C to +35°C (fanless) up to +50°C (internal fan)
Operation	-30°C - +80°C
Storage	95% (non-condensing)
Humidity	

Order information

REF	DESCRIPTION
TF01013	APT IP Codec with AC PSU
TF01013-DC	APT IP Codec with DC PSU
CD00123	SureStream Technology license (secure redundant streaming)
SP02701	SynchroStream Kit (precision GPS-based synchronicity)
LC00074	Digital MPX/composite license for linear MPX and APTmpX

This document is not contractual. All specifications are subject to change without notice.

Headquarters

20 avenue Neil Armstrong
33700 Mérignac (Bordeaux) **FRANCE**
+33 (0)5 57 928 928

US Subsidiary

20233 NE 15th Court
Miami, FL 33179 **USA**
+1 305 249 3110

